



Technical drawing of the front view of a transformer. The drawing includes the following dimensions and callouts:

- Overall width: 5535
- Width of the central core: 4525
- Height of the top section: 1835
- Height of the bottom section: 3700
- Height of the bottom section (excluding the base): 820
- Overall height: 5535
- Overall width (including base): 5580
- Callouts: 11, 7, 6, 16, and "B"

項	名	稱	材 質	尺 寸	件數
	Description		M.T	Specification	Q'ty
1	馬達	Fan Motor		20HPx6P	4 個 PCS
2	減速機	Belt Reducer		VBA-150BL	4 座 SET
3	馬達架	Motor Frame	H.D.G.S		4 組 SET
4	出風口網	Fan Guard	H.D.G.S		4 組 SET
5	風扇	Fan	A.C.	LSF-360	4 組 SET
6	散熱片	Filling	P.V.C.		4 組 SET
7	散水箱	Distribution Box	F.R.P.		16個 PCS
8	風洞	Fan Stack	F.R.P.		4 組 SET
9	階梯	Ladder	H.D.G.S		2 組 SET
10	水槽	Water Sump	F.R.P.		8 個 PCS
11	溫水入管	Inlet Pipe Connection	H.D.G.S	6 B	16支 PCS
12	冷水出管	Outlet Pipe Connection	H.D.G.S	8 B	8 支 PCS
13	自動補給水管	Automatic Filler	NYLON	1 1/2 B	8 支 PCS
14	手動補給水管	Quick Filler	NYLON	1 1/2 B	8 支 PCS
15	溢水管	Overflow	NYLON	2 B	8 支 PCS
16	排水管	Drain	ST.S	2 B	8 支 PCS

Abbrev. : 1. H.D.G.S.: Hot Dip Galvanized Steel
熱浸鍍鋅鐵
2. A.C. : Aluminum Alloy Cast
鋁合金
3. ST.S : Stainless Steel 304
不銹鋼
4. F.R.P. : Fiberglass Reinforced Plastic
玻璃纖維強化塑膠

Remark : (*)Inlet Pipe Connection to be Supplied by Customer.
註：溫水入管由客戶提供

冷卻塔空重 Dry weight : 16200 kg		運轉重量 Operating Weight : 41400 kg	
荷重 Loading Data			
外氣濕球溫度 Ambient Wetbulb Temp: 27°C		風量 Air Volume : 3500M ³ /MIN/CELL	
出水溫度 Outlet Water Temp: 32°C		水量 Water Flow : 31200 LPM	
入水溫度 Inlet Water Temp: 37°C		冷卻能力 Cooling Capacity : 9360000Kcal/HR	
設計基準 Design Condition			
變更號碼	日 期	變 更	核 對 核 准 記 事 NOTE
圖 名 TITLE	LRC-N-600-C4		
	外觀圖 OUTLINE VIEW		
核 定			MM 1 / 150 102 • 10 • 1
校 對		製 圖 陳 建 宏	圖 號 DWG NO.
良機實業股份有限公司 LIANG CHI INDUSTRY CO., LTD.			31-123-1802